



**ENTERPRISE TIME
RECORDING
SOLUTIONS INC.**

Enterprise Time Recording Solutions HandPunch 3000 Biometric Time & Attendance Terminal

Put your hands on the accurate, affordable solution.

Enterprise Time Recording Solutions HandPunch 3000

Ingersoll Rand Recognition Systems now brings the accuracy and convenience of biometric technology easily within reach of any time and attendance applications. In operations that range from coal mines to clean rooms, Ingersoll Rand Recognition Systems have proven themselves to be a practical and precise solution. Our terminals are so affordable, it doesn't make sense to consider any other technology.



Smarter than card-based terminals

There are no cards to create, administer, carry – or lose. The HandPunch® 3000 verifies employees' identities in less than one second, based on the unique size and shape of their hands. HandPunch 3000 clearly notifies each user of a match using red and green indicator lights. Because no one can punch in or out for your employees, the system reduces time theft and improves payroll accuracy.

Versatile and programmable

Beyond a simple time clock, the HandPunch 3000 provides definable data management keys that allow data collection when employees punch. The readers transmit data to the time and attendance host PC through a variety of methods including direct wiring, modem and Ethernet. The HandPunch 3000 also has the ability to control a door. When you want to cut time and attendance costs...do it by hand.

Enterprise Time Recording Solutions HandPunch 1000E

FEATURES AND BENEFITS

- ▶ Saves money over card-based systems
- ▶ Eliminates Badges
- ▶ Eliminates Buddy Punching
- ▶ Fast and easy to use
- ▶ Provides the most accurate time and attendance solution available

Hand Geometry Technology

The HandPunch® 3000 uses Ingersoll Rand Recognition Systems' field-proven hand geometry biometric technology. The terminal captures a three-dimensional image of the hand each time the employee punches. The hand's size and shape are used to verify their identity with unparalleled accuracy. No fingerprints or palm prints are utilized. Green and red lights notify the employee of the status of each punch. There's no question any more; employees have to be there to punch.

Programmable Data Management Keys

The HandPunch 3000 has two user-definable data management keys that let you collect data as employees punch. Common uses include department transfers, tips collected, job codes, or pay codes. Multilevel data entry sequences may be defined. You can also set the data management keys to allow employees to review their past punches. To reduce keystrokes, the keys can also be set to automatically enter data such as a frequently used department number or in/out status.

Communication Options

Whether your application calls for one terminal or thousands, the HandPunch 3000 can meet the need. Multiple terminals can be networked together at a site via RS-485 wiring. An optional Ethernet communications module or dial up modem are also available. Both options are internal to the terminal making installation fast and simple.

Edit-at-the-Clock Functions

The HandPunch 3000 allows supervisors to override user restrictions and to input such items as missed punches, planned vacations, and sick time at the terminal. The password-protected mode provides greater supervisor flexibility by lessening the need for computer edits. Audit trails documenting the use of these functions are generated to ensure security.

Bell Schedules

The bell schedule lets you program the day, time and duration of a series of bells. The bells can be programmed to signal the beginning or end of a shift, lunch or break.

Door Control

The HandPunch 3000 provides the capability to unlock and monitor a door. Global timezones may be used to restrict employee access.

SPECIFICATIONS

Part Number: HP-3000

Size: 8.85 in (22.3 cm) wide, 11.65 in (29.6 cm) high
8.55 in (21.7 cm) deep

Weight: 6 lbs (2.7 kg)

Power: 12 to 24 VDC or 12 to 24 VAC 50-60 Hz, 7 watts

Environment: Operating: 32°F to 113°F (0°C to 45°C)

Relative Humidity: 20% to 80% NC

Non-operating (storage): 14°F to
140°F (-10°C to 60°C)

Relative Humidity: 5% to 85% NC

Verification Time: Less than one second

Memory Retention: Up to 5 years via the standard internal lithium battery.

Transaction Storage: 5120 transactions

ID Number Length: 1 to 10 digits from keypad or card

User Capacity: 512 users expandable to 32,512 users

Template Size: 9 bytes

Communications: RS-485 (4 and 2 wire)

RS-232 Serial Printer Support or network communications

Baud Rate: 300 to 28.8 Kbps

Card Reader Input: Proximity, Wiegand, Magnetic Stripe,
Bar Code (5 VDC provided by HandReader)

Card Reader Output: Wiegand, Magnetic Stripe, Bar Code

Duress Code: 1 leading digit (user definable)

Door Controls: Door Lock Output

(Sinks 0-24VDC, 100mA max)

Door Switch Monitoring

Bell Ring Output

(Sinks 0-24VDC, 100mA max)

Time Zones: 62 user definable time zones

Options: BB-200 Operational Battery Backup

BC-100 Bar Code Reader Wall Mount

DC-102 Data Converter (RS-232 to RS-485)

EM-801 Memory Expansion - 9,728 users

EM-803 Memory Expansion - 32,512 users

EN-200 Ethernet Communications Module

MD-500 Internal 14.4 Baud Dial-up Modem

WAR-EXT 1 year extended warranty



Enterprise Time Recording Solutions Inc.

Head Office: 237 Romina Drive, Suite 201 & 202 Vaughan, Ontario, Canada L4K 4V3

Phone: (905) 660 6167 Fax: (905) 660 4810 Toll Free: (877) 660 TIME (8463)

Website: www.enterprisetime.ca | Authorized Ingersoll Rand Dealer